



NTA855-G7 Advantage Data Sheet

Cummins Engine Company, Inc. Columbus, Indiana 47201


Curve Number: FR-10348	Engine Critical Parts List: CPL 2939	Date: 12Apr04
Displacement : 14.0 litre (855.0 in³)	Bore : 140 mm (5.5 in.)	Stroke : 152 mm (6.0 in.)
No. of Cylinders : 6	Aspiration : Turbocharged and Aftercooled	

•• PRELIMINARY ••
Emergency Standby Ratings for application in Corporate Generator Sets Only

Engine Speed	Standby Power	
RPM	kWm	BHP
1500	391	525

Engine Performance Data @ 1500 RPM

OUTPUT POWER			FUEL CONSUMPTION			
%	kWm	BHP	kg/ kWm-h	lb/ BHP-h	litre/ hour	U.S. Gal/ hour
STANDBY POWER						
100	391	525	0.212	0.349	97.7	25.8
75	293	393	0.208	0.343	72.0	19.0
50	195	262	0.217	0.357	50.0	13.2
25	97	131	0.224	0.369	25.7	6.8



PAIVAR DIESEL ASIA

CONVERSIONS: (Litres = U.S. Gal x 3.785) (Engine kWm = BHP x 0.746) (U.S. Gal = Litres x 0.2642) (Engine BHP = Engine kWm x 1.34)

Data shown above represent gross engine performance capabilities obtained and corrected in accordance with ISO-3046 conditions of 100 kPa (29.53 in Hg) barometric pressure [110 m (361 ft) altitude], 25 °C (77 °F) air inlet temperature, and relative humidity of 30% with No. 2 diesel or a fuel corresponding to ASTM D2. See reverse side for application rating guidelines.
 The fuel consumption data is based on No. 2 diesel fuel weight at 0.85 kg/litre (7.1 lbs/U.S. gal).
 Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan, optional equipment and driven components.

D.K. Trueblood
CHIEF ENGINEER



NTA855-G7 Advantage Data Sheet

Cummins Engine Company, Inc. Columbus, Indiana 47201


•• PRELIMINARY ••

POWER RATING APPLICATION GUIDELINES FOR EMERGENCY STANDBY ENGINES FOR APPLICATION IN CORPORATE GENERATOR SETS ONLY

These guidelines have been formulated to ensure proper application of generator drive engines in Cummins corporate generator set installations. Generator drive engines are not designed for and shall not be used in variable speed D.C. generator set applications.

Applicable for supplying emergency power for the duration of the utility power outage. No overload capability is available for this standby rating. Under no condition is an engine allowed to operate in parallel with the public utility at the Emergency Standby Power rating. This rating should be applied where reliable utility power is available. An emergency standby rated engine should be sized for a maximum of an **70%** typical load factor and **200 hours** of operation per year. This includes a maximum of **1 hour** in a **12 hour** period at the Emergency Standby Power rating. Emergency Standby rating should never be applied except in true emergency power outages. Negotiated power outages contracted with a utility company are not considered an emergency.

Standby Power Derate Curve



Reference Standards:

BS-5514 and DIN-6271 standards are based on ISO-3046.

Operation At Elevated Temperature And Altitude:

For sustained operation above these conditions, derate by 4% per 1000 ft (300 m) and 8.3% per 10 °F (15% per 10 °C).



NTA855-G7 Advantage Data Sheet

Cummins Engine Company, Inc. Columbus, Indiana 47201

•• PRELIMINARY ••

Cummins Engine Company, Inc. Engine Data Sheet

ENGINE MODEL : **NTA855-G7**

CONFIGURATION NUMBER : D093629DX02

DATA SHEET : DS-10348

DATE : 12Apr04

PERFORMANCE CURVE : FR-10348

INSTALLATION DIAGRAM

• Fan to Flywheel : TBD

CPL NUMBER

• Engine Critical Parts List : 2939

GENERAL ENGINE DATA

Type.....	4-Cycle; In-line; 6-Cylinder Diesel
Aspiration.....	Turbocharged and Aftercooled
Bore x Stroke..... — in x in (mm x mm)	5.5 x 6.0 (140 x 152)
Displacement..... — in ³ (liter)	855 (14.0)
Compression Ratio.....	14.0 : 1
Dry Weight	
Fan to Flywheel Engine..... — lb (kg)	2900 (1315)
Wet Weight	
Fan to Flywheel Engine..... — lb (kg)	3018 (1369)
Moment of Inertia of Rotating Components	
• with FW 1109 Flywheel..... — lb _m • ft ² (kg • m ²)	118.5 (4.99)
Center of Gravity from Rear Face of Flywheel Housing..... — in (mm)	27.7 (704)
Center of Gravity above Crankshaft Centerline..... — in (mm)	5.5 (140)
Maximum Static Loading at Rear Main Bearing..... — lb (kg)	N.A.

ENGINE MOUNTING

Maximum Bending Moment at Rear Face of Block..... — lb • ft (N • m)	1000 (1356)
---	-------------

EXHAUST SYSTEM

Maximum Back Pressure..... — in Hg (mm Hg)	3 (76)
--	--------

AIR INDUCTION SYSTEM

Maximum Intake Air Restriction	
• with Dirty Filter Element..... — in H ₂ O (mm H ₂ O)	25 (635)
• with Normal Duty Air Cleaner and Clean Filter Element..... — in H ₂ O (mm H ₂ O)	10 (254)
• with Heavy Duty Air Cleaner and Clean Filter Element..... — in H ₂ O (mm H ₂ O)	15 (381)

COOLING SYSTEM

Coolant Capacity - Engine Only..... — US gal (liter)	5.5 (20.8)
Maximum Coolant Friction Head External to Engine - 1500 rpm..... — psi (kPa)	6 (41)
Maximum Static Head of Coolant Above Engine Crank Centerline..... — ft (m)	60 (18.3)
Standard Thermostat (Modulating) Range..... — °F (°C)	180 - 200 (82 - 93)
Minimum Pressure Cap..... — psi (kPa)	10 (69)
Maximum Top Tank Temperature for Standby..... — °F (°C)	220 (104)

LUBRICATION SYSTEM

Oil Pressure @ Idle Speed..... — psi (kPa)	15 (103)
@ Governed Speed..... — psi (kPa)	35 - 45 (241 - 310)
Maximum Oil Temperature..... — °F (°C)	250 (121)
Oil Capacity with OP 1396 Oil Pan : High - Low..... — US gal (liter)	9.0 - 8.0 (34.1 - 30.3)
Total System Capacity (Including Combo Filter)..... — US gal (liter)	9.7 (36.7)
Angularity of OP 1396 Oil Pan — Front Down.....	45°
— Front Up.....	45°
— Side to Side.....	45°



NTA855-G7 Advantage Data Sheet

Cummins Engine Company, Inc. Columbus, Indiana 47201

FUEL SYSTEM

Type Injection System.....	Direct Injection Cummins PT
Maximum Restriction at PT Fuel Injection Pump — with Clean Fuel Filter..... — in Hg (mm Hg)	4.0 (102)
— with Dirty Fuel Filter..... — in Hg (mm Hg)	8.0 (203)
Maximum Allowable Head on Injector Return Line (Consisting of Friction Head and Static Head)..... — in Hg (mm Hg)	6.0 (152)
Maximum Fuel Flow to Injection Pump..... — US gph (liter / hr)	98 (372)

ELECTRICAL SYSTEM

Cranking Motor (Heavy Duty, Positive Engagement)..... — volt	24
Battery Charging System, Negative Ground..... — ampere	35
Maximum Allowable Resistance of Cranking Circuit..... — ohm	0.002
Minimum Recommended Battery Capacity	
• Cold Soak @ 50 °F (10 °C) and Above..... — 0°F CCA	600
• Cold Soak @ 32 °F to 50 °F (0 °C to 10 °C)..... — 0°F CCA	640
• Cold Soak @ 0 °F to 32 °F (-18 °C to 0 °C)..... — 0°F CCA	900

COLD START CAPABILITY

Minimum Ambient Temperature for Aided (with Coolant Heater) Cold Start within 10 seconds..... — °F (°C)	50 (10)
Minimum Ambient Temperature for Unaided Cold Start..... — °F (°C)	40 (4)

PERFORMANCE DATA

All data is based on:

- Engine operating with fuel system, water pump, lubricating oil pump, air cleaner and exhaust silencer; not included are battery charging alternator, fan, and optional driven components.
- Engine operating with fuel corresponding to grade No. 2-D per ASTM D975.
- ISO 3046, Part 1, Standard Reference Conditions of:

Barometric Pressure : 100 kPa (29.53 in Hg)	Air Temperature : 25 °C (77 °F)
Altitude : 110 m (361 ft)	Relative Humidity : 30%

Steady State Stability Band at any Constant Load..... — %	+/- 0.25
Estimated Free Field Sound Pressure Level of a Typical Generator Set;	
Excludes Exhaust Noise; at Rated Load and 7.5 m (24.6 ft); 1800 rpm / 1500 rpm..... — dBA	N/A / 90.3
Exhaust Noise at 1 ft. Horizontally from Centerline of Exhaust Pipe Outlet Upwards at 0°..... — dBA	124

Governed Engine Speed..... — rpm	
Engine Idle Speed..... — rpm	
Gross Engine Power Output..... — BHP (kW _m)	
Brake Mean Effective Pressure..... — psi (kPa)	
Piston Speed..... — ft / min (m / s)	
Friction Horsepower..... — HP (kW _m)	
Engine Water Flow at Stated Friction Head External to Engine:	
• 2 psi Friction Head (estimated)..... — US gpm (liter / s)	
• Maximum Friction Head (estimated)..... — US gpm (liter / s)	

STANDBY	
50 hz	
	1500
	575 - 675
	525 (369)
	324 (2234)
	1500 (7.6)
	38 (28.9)
	105 (6.6)
	94 (5.9)
	1115 (526)
	1030 (553)
	2975 (1403)
	3378 (59)
	11750 (207)
	19890 (349)

Engine Data with Dry Type Exhaust Manifold

Intake Air Flow..... — cfm (liter / s)	
Exhaust Gas Temperature..... — °F (°C)	
Exhaust Gas Flow..... — cfm (liter / s)	
Radiated Heat to Ambient..... — BTU / min (kW _m)	
Heat Rejection to Coolant..... — BTU / min (kW _m)	
Heat Rejection to Exhaust..... — BTU / min (kW _m)	

N.A. - Data is Not Available
N/A - Not Applicable to this Engine
TBD - To Be Determined

•• PRELIMINARY ••